KOHLER SDMO



PERFORM 7500 T C5

PORTABLE POWER

GENERATING SET Range PERFORM

PRODUCT ADVANTAGES

Compact frame with protection panels against shocks

• Starting up facilitated thanks to the summer/winter positions

- KOHLER air-cooled industrial engine
- · Good value for money
- Generating set guaranteed 3 years

QUAD CLEAN AIR FILTER The Cyclonic Quad Clean air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine, fuel economies, increase the engine performance and extend its lifetime

OVERSIZED ALTERNATOR The oversized alternator is ideal for supplying electronic equipment and secures the engines sypplying. It has very low harmonic current and limits the voltage and frequency variation of the power supplied as well as handling high surge loads.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range PERFORM

An efficient, cost effective and easy to handle equipment, suitable for frequent use.



PERFORM 7500 T C5

GENERAL SPECIFICATIONS

Range	PERFORM
Frequency (Hz)	50 Hz
Max power (kW) *	6,50
Max power (kVA)	8,10
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	7,30
75% cons. (l/h) *	2,60
75% Autonomy (h) *	2,80
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	CH440_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	429
Oil system capacity including filters (I)	1,30

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	55,50
Height (cm)	59
Dry Weight (kg)	93,50

PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56,50
Height (cm)	60
Weight (kg)	95,50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	583



PERFORM 7500 T C5 - PORTABLE POWER - GENERATING SET PERFORM

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com





27/05/202 PERFORM 7500 T C5 - PORTABLE POWER - GENERATING SET PERFORM This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



PERFORM 7500 T C5

ACCESSORIES SUPPLIED					
	Funnel		User and maintenance manual		
	Floor maintaining slot		Ergonomic handle grip		
OPTIONS					
	R03	This set includes the hour meter and the differe	ntial circuit breaker.		
	RKB1HD	Trolley kit for the generating sets of 6kW or belo	w		
	RKS2	Maintenance kit for KOHLER CH395 and CH4	40 engines.		
at your	RH1	Cover for SDMO 's generating sets, welding set	ts and water pumps		
	RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V			
	RPQ	For earthing your generator set. Galvanised 1 n supplied with 2 m of 10 mm ² cable.	n long spike,		
	RBAC	Removable storage box			



PERFORM 7500 T C5 - PORTABLE POWER - GENERATING SET PERFORM This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com