



TECHNIC 15000TA C5

PORTABLE POWER

GENERATING SET Range TECHNIC

PRODUCT ADVANTAGES

- Generating set guaranteed 3 years
- KOHLER air-cooled industrial engine
- Electric starter with batteries without maintenance
- Large Autonomy
- Connection interface equipped with an hour meter and the APM202 control unit

GENERATOR SMART CARE is a Bluetooth box which can be used on all the brand's portable generators.TECHNOLOGY EQUIPPED WITH AN INNOVATIVE APPLICATION Generator Smart Care is a digital solution which provides access to:- The list of generators- The maintenance due dates- A maintenance aid- The map of reseller partners STAGE V (2016/1628 EU): This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature

Range TECHNIC

A long run time equipment that can withstand extreme conditions, for daily professional use.



















TECHNIC 15000TA C5

GENERAL SPECIFICATIONS

Range	TECHNIC
Frequency (Hz)	50 Hz
Max power (kW) *	11,50
Max power (kVA)	14,40
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	35
75% cons. (I/h) *	5
75% Autonomy (h) *	7
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	CH680_C5
Engine Type	O.H.V.
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	674
Oil system capacity including filters (I)	1,90

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + APM202

DIMENSIONS AND WEIGHT

Length (cm)	89,50
Width (cm)	57
Height (cm)	77
Dry Weight (kg)	172

PACKAGING

Box / Pallet
91
58,50
92
189
0
0
0





TECHNIC 15000TA C5

ACCESSORIES SUPPLIED



Funnel

RKS5

RPM



Battery without maintenance



User and maintenance manual

Hour meter



This set includes a differential switch, a hour meter, the plugs and a R₀3B

thermal circuit breaker.



Remote control in order to start or stop the generating set until a **RSTART2** distance of 50 meters (needs the APM202 control panel)



RKB2 Trolley kit for the generating sets superior to 6kW



Maintenance kit for KOHLER CH680 engine.



The adaptor for industrial sockets is used to connect 230-V **RAP** appliances to the industrial socket.



RH₂ Cover for SDMO 's generating sets, welding sets and water pumps



Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V

