



VX 200/4 C5

PORTABLE POWER

WELDING SET Range WELDARC INTENS


PRODUCT ADVANTAGES

- HONDA Professional Engine
- Generating set guaranteed 3 years
- Light storage box integrated
- Solid and high-performance equipment
- Auxiliary Single phase output

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range WELDARC INTENS

Welding sets which can be used on sites where there is no electricity.



VX 200/4 C5

WELDING SET SPECIFICATIONS

Range	WELDARC INTENS
Frequency (Hz)	50 Hz
Max power (kW) *	4
Max power (kVA)	4
Normal duty cycle 35% (A)	200
Intensif duty cycle 60% (A)	170
Stricking volts (V)	75
Rods diameter mini (mm)	1.6
Rods diameter maxi (mm)	4
Fuel	Petrol
Tank (L)	6,10
75% cons. (l/h) *	2,50
75% Autonomy (h) *	2,40
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	389
Oil system capacity including filters (l)	1,10

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	88
Width (cm)	57
Height (cm)	55,50
Dry Weight (kg)	87

PACKAGING

Packaging type	Box / Pallet
Length (cm)	88
Width (cm)	58,50
Height (cm)	70
Weight (kg)	100
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0



27/05/2022

VX 200/4 C5 - PORTABLE POWER - WELDING SET WELDARC INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Storage box



User and maintenance manual

OPTIONS



R01 This set includes the hour meter and the differential circuit breaker.



RKB2 Trolley kit for the generating sets superior to 6kW



R10 Welding kit includes 2 x 5 m of cable, 1 earth clip, 1 electrode holder, 1 hammer, 1 brush and 1 mask.



R19 Maintenance kit for Honda GX390 engines (except Alizé 6000E and Alizé 7500 TE)



RBH1 Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5 Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RH2 Cover for SDMO 's generating sets, welding sets and water pumps



RPQ For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.



RKD1 kit of two diferential removable adapters for domestic sockets. Schema for ground bonding with isolated neutral